

EUROVAC Eurovac Pressure Washer Systems

1 Tech Central Pressure Washer Systems

Description	Eurovac Part No.
 Operator 3HP Pressure Wash System (460/3/60) 4 gpm @ 1100 psi maximum Wall mounted (floor mount available upon request) Automatic start/stop with off delay timer Automatic high temp shut down (145deg) Belt driven ceramic plunger pump Adjustable pressure regulator with bypass hose Back up safety relief valve Discharge pressure gauge Heavy duty base/frame with bibration isolation pads and protective pump cover Water Requirement: 3/4" Line - 40 to 60 psi. If not available, see feed tank option 	SYS-PRE- 103H4603
1 Operator 3HP Pressure Wash System (575/3/60) • SAME AS ABOVE	SYS-PRE- 103H5753
1 Operator 3HP Pressure Wash System (230/1/60) • SAME AS ABOVE	SYS-PRE- 103H2301

2 Tech Central Pressure Washer Systems

Description	Eurovac Part No.
 2 Operator 7.5HP Pressure Wash System (460/3/60) 8 gpm @ 1200 psi maximum Wall mounted (floor mount available upon request) Automatic start/stop with off delay timer Automatic high temp shut down (145deg) Belt driven ceramic plunger pump Adjustable pressure regulator with bypass hose Back up safety relief valve Discharge pressure gauge Heavy duty base/frame with bibration isolation pads and protective pump cover Water Requirement: 3/4" to 1" Line - 40 to 60 psi. If not available, see feed tank option 	SYS-PRE- 207H4603
2 Operator 7.5HP Pressure Wash System (575/3/60) • SAME AS ABOVE	SYS-PRE- 207H5753
2 Operator 7.5HP Pressure Wash System (230/1/60) • SAME AS ABOVE	SYS-PRE- 207H2301

3 Tech Central Pressure Washer Systems

Description	Eurovac Part No.
 3 Operator 10HP Pressure Wash System (460/3/60) 12 gpm @ 1200 psi maximum Wall mounted (floor mount available upon request) VFD controlled (for energy saving and extended system conponent life) Automatic start/stop with off delay timer Automatic high temp shut down (145deg) Belt driven ceramic plunger pump Adjustable pressure regulator with bypass hose Back up safety relief valve Discharge pressure gauge Heavy duty base/frame with bibration isolation pads and protective pump cover Water Requirement: 1" to 1-1/4" Line - 40 to 60 psi. If not available, see feed tank option 	SYS-PRE- 310H4603
3 Operator 10HP Pressure Wash System (575/3/60) SAME AS ABOVE	SYS-PRE- 310H5753
3 Operator 10HP Pressure Wash System (230/1/60) • SAME AS ABOVE	SYS-PRE- 310H2301

4 Tech Central Pressure Washer Systems

Description	Eurovac Part No.
 4 Operator 20HP Pressure Wash System (460/3/60) 16 gpm @ 1800 psi maximum Wall mounted (floor mount available upon request) VFD controlled (for energy saving and extended system conponent life) Automatic start/stop with off delay timer Automatic start/stop with off delay timer Automatic high temp shut down (145deg) Belt driven ceramic plunger pump Adjustable pressure regulator with bypass hose Back up safety relief valve Discharge pressure gauge Heavy duty base/frame with bibration isolation pads and protective pump cover Water Requirement: 1-1/4" to 1-1/2" Line - 40 to 60 psi. If not available, see feed tank option 	SYS-PRE- 420H4603
4 Operator 20HP Pressure Wash System (575/3/60) • SAME AS ABOVE	SYS-PRE- 420H5753

Heaters (Optional Addition)

Description	Eurovac Part No.
 72 Kw Dual Heat Exchanger (460/3/60) Dual 316 stainless steel coils in heat exchanger Fully automatic operation Fully insulated for maximum efficiency Low water safety shut off in heater tank Adjustable temperature control Tube type incoloy elements Safety relief valve (brass) QTY2 - 3/8" x 6' Jumper hoses Includes perma film to prevent galvanic reaction/corrosion 	SYS-PRE- HE72KW04
72Kw Dual Heat Exchanger (575/3/60) • SAME AS ABOVE	SYS-PRE- HE72KW05
72Kw Dual Heat Exchanger (208/230/3/60) • SAME AS ABOVE	SYS-PRE- HE72KW02

Feed Tanks (Optional Addition)

Description	Eurovac Part No.
 1 to 2 Operator - 50 Gallon Feed Tank For facilities with minimal water INCLUDES: Inlet water float valve Pilot line for system activation Low water level shut down and auto reset Misc plumbing (hose & fittings for inlet, discharge & bypass ports) 24v relay and terminal in control box Powder coat painted stand 	SYS-PRE- FT050000
 3 Operator - 100 Gallon Feed Tank For facilities with minimal water INCLUDES: SAME AS ABOVE 	SYS-PRE- FT100000
 4 Operator - 200 Gallon Feed Tank For facilities with minimal water INCLUDES: SAME AS ABOVE 	SYS-PRE- FT200000

Hose, Holster & Gun Assembly

Description	Eurovac Part No.
Hose, Holster & Gun Assembly • 3/8" x 50' High Pressure Hose • Stainless Steel Holster • High Pressure Wand/Gun with Nozzle	SYS-PRE- WMK00000

Overhead Boom Assembly

	Description	Eurovac Part No.
15-	Overhead Boom Assembly • 6' x 360 Degree Galvanized Steel Boom • 6' x 3/8" Jumper Hose • 3/8" x 15' High Pressure Hose • Gun Holster • High Pressure Wand/Gun with Nozzle • Stainless Steel Swivel • NOTE: Boom to be mounted at 14' Max off floor	SYS-PRE- OHK00360
	Overhead Stainless Steel Boom Assembly 6' x 360 Degree Polished Stainless Steel Boom 6' x 3/8" Jumper Hose 3/8" x 15' High Pressure Hose Stainless Steel Holster High Pressure Wand/Gun with Nozzle Stainless Steel Swivel NOTE: Boom to be mounted at 14' Max off floor	SYS-PRE- OHKSS360
	6' Boom Support Bracket (inc. cross bracing both ways)	SYS-PRE- OHB06000
	3/4" x 10' Cross Bracket (One Side Of Bracket)	Misc

Car Wash Soap Injector

1.4	Description	Eurovac Part No.
	Car Wash Soap Injector • Includes a flow ball valve for the selection of chemical or rinse mode •When cleaning in chemical mode, system will reduce the pressure at that drop by approximately 35%	SYS-PRE- CW100000

Additional Items

EUROVAC	Description	Eurovac Part No.
	Stainless Steel Holster • For high pressure wand/gun assembly • Wall mount	SYS-PRE- SSH00000
	 PVC Holster For high pressure wand/gun assembly Wall mount 	SYS-PRE- PVCH0000
5	Description	Eurovac Part No.
Q	 3/8" x 6' High Pressure Jumper Hose To connect from distribution piping to booms or hose reels To connect from distribution piping to system 	SYS-PRE- 20611900
	Description	Eurovac Part No.
	Pulsation Surge Arrestor • Reduces pump pulsation and contributes to quieter operation and extended components life.	SYS-PRE- SA000000
	3/8" x 50' High Pressure Hose Assembly	SYS-PRE- 20088100
	Wand/Gun Ball Valve & Disconnect • 2000psi stainless steel 1/2" ball valve & quick connect	SYS-PRE- 12BV0QC0

Pressure Washer Work Stations

Work Station	Description	Eurovac Part No.
WORK Station	IStainless Steel Work Station	SYS-PRE- WK0SS000