

EUROVAC II - 4 MAN CENTRAL VACUUM SYSTEM

Eliminate sanding & grinding dust with a Eurovac Central Vacuum System



PRODUCT DESCRIPTION

- **Powerful 5HP Pump** produces, 125" of water column and 232" of free flow CFM.
- **Superior Filtration** ... Cyclonic filtration removes 99% of dust before the secondary filter. This results in the unit operating much more efficiently than units which do not have cyclonic filtration. The remaining 1% of dust is removed by a secondary cartridge filter which cleaned by compressed air pulse jet cleaning action.
- **Quiet** ... Muffler and insulated motor housing reduce noise level below 65 dBA's
- **Properly Engineered Pipe** ... graduated 3" to 2" pipe maintains optimum velocity and reduces friction losses significantly compared to systems with 2" piping only
- **On/Off feature** ... Micro switch turns system on and off when hoses is plugged into the inlet.
- **Easy to Install** ... complete installation instruction included.



The very affordable Dust Extraction System

- A low cost solution to sanding and grinding dust problems
- Most sanding and grinding dust is harmful
- A properly installed Eurovac II system virtually eliminates sanding dust
- Sandpaper costs are reduced because sandpaper lasts up to 40% longer
- Better finish - reduces grit build-up which causes swirl marks
- Cuts clean up costs and increases production